



适用机型：饮水机、饮料/啤酒柜、冰箱、冷柜

Suitable machines: Water dispensers, Bottlecoolers, Refrigerators, Freezers

应用范围：低背压、中背压、高背压

Applications: LBP, M/HBP

制冷剂Refrigerants: R134a, R600a, R290

可用电压Available voltage: 220-240V/50-60Hz, 110-120V/50-60Hz

制冷剂 Refrigerant	制冷量范围 Capacity Range								能效Efficiency				容积 Displacement (CM ³)		马力 HP			
	LBP				M/HBP				LBP		M/HBP							
	最小Min		最大Max		最小Min		最大Max		普效 OE	高效 HE	普效 OE	高效 HE	最小Min	最大Max	最小Min	最大Max		
	W	BTU/h	W	BTU/h	W	BTU/h	W	BTU/h	COP	EER	COP	EER						
R134a	55	187.6	135	406.6	245	836	465	1586.6	1.05	3.58	1.30	4.43	1.00	3.41	2.5	5.7	1/12	1/5-
R600a	56	191	130	443.5	/	/	/	/	1.20	4.09	1.35	4.6	/	/	3.5	7.5	1/12	1/6-
R290	/	/	132	450	/	/	/	/	1.30	4.43	/	/	/	/	/	3.0	/	1/12+

★ Capacity @ -23.3°C for LBP, 7.2°C for M/HBP.